# WAC LIGHTING

## WL-LED200TR

# Step And Wall Light

1 0			
Model & Voltage	Color Temp & CRI	Lumens	Finish
O WL-LED200TR 120 VAC	O Red 90	72	O WT White on
	OBlue 90	72	Aluminum
	OAmber 90	72	
	O3000K 90	72	
	O 2700K 90	72	

Example: WL-LED200TR-27-WT

## **FEATURES**

- Can be painted to match the color of the surface
- Low profile, flush to wall aesthetics with no visible hardware
- Balanced lighting, free of shadows with minimum glare
- Up to 200 fixtures can be connected in parallel
- 5 year warranty

#### **SPECIFICATIONS**

**Construction** Die-cast corrosion resistant aluminum alloy

Power: 3.3W

Input: 120 VAC,50/60Hz
Dimming: ELV: 100-10%
Light Source: Integrated LED
Rated Life: 50,000 Hours

**Mounting:** Fits into 2" x 4" J-Box with minimum inside dimensions of 3"L x

2"W x 2"D

Finish: Enamel Coated White on Aluminum

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Damp Location Listed, ADA, Title 24 JA8 Compliant

## **REPLACEMENT PARTS**

RM-1X4-30-200TR - 120V Replacement Module



#### **FINISHES:**

Fixture Type:

Project:

Location:

Catalog Number:



White on Aluminum

#### LINE DRAWING:

